
CNC 泛用精密虎鉗 5 Axis Vise CNC Flexible Vise





■ 特點

- 1. 泛用四軸、五軸、CNC 分度盤 立臥式 CNC 銑床之精密加工。
- 2. 特殊材質 FCD60 鑄鐵, 專利機身 結構,穩固不易變形。
- 3. 滑動面經熱處理 HRC45°以上, 全鋼製鉗口,熱處理 HRC50° 替換彈性運用廣泛。


Features

- 1. Suitable to be used in 4 and 5 Axis CNC Rotary Table, either in horizontal or vertical machining.
- 2. Vise body is made of high malleable iron FCD60, delicately designed structure, ensures working precision and enhances rigidity for long service life.
- 3. Sliding surfaces are hardened to HRC 45°, flexible designed vise jaw is made by high quality steel and hardened HRC 50°.

| ITEM NO. 型號 | X- 3 |
|----------------|------|
| А | 207 |
| В | 180 |
| С | 80 |
| D | 58 |
| D1 | 118 |
| E | 60 |
| F | 60 |
| G | 8 |
| Н | 70 |
| I | 20 |
| J | 100 |
| K | 15 |
| M | 18 |
| N | 29 |
| 0 | 13 |
| Р | 115 |
| Weight 重量 | 8kg |

同動求心虎鉗 5 Axis Vise Self Centering Vise





- 1. 泛用四軸、五軸、CNC 分度盤、 立臥式 CNC 銑床之精密加工。
- 2. 特殊材質 FCD60 鑄鐵, 專利機身 結構,穩固不易變形。
- 3. 滑動面經熱處理 HRC45°以上, 全鋼製鉗口,熱處理 HRC50° 替換彈性運用廣泛。

Features

- 1. Suitable to be used in 4 and 5 Axis CNC Rotary Table, either in horizontal or vertical machining.
- 2. Vise body is made of high malleable iron FCD60, delicately designed structure, ensures working precision and enhances rigidity for long service life.
- 3. Sliding surfaces are hardened to HRC 45°, flexible designed vise jaw is made by high quality steel and hardened HRC 50°.

| ITEM NO. 型號 | DX- 3 |
|----------------|-------|
| А | 207 |
| В | 180 |
| С | 80 |
| D | 58 |
| D1 | 118 |
| E | 60 |
| F | 60 |
| G | 8 |
| Н | 70 |
| I | 30 |
| J | 100 |
| K | 15 |
| М | 18 |
| 0 | 13 |
| Р | 115 |
| Weight 重量 | 10kg |